

Drying

Drying

Objectives of Drying

1. **Preservation:** Removing moisture from materials to prevent spoilage and microbial growth.
2. **Weight Reduction:** Reducing the weight for easier handling, storage, and transportation.
3. **Volume Reduction:** Decreasing the volume for efficient storage and packaging.
4. **Consistency:** Achieving a specific consistency or texture in products, particularly in food processing.
5. **Preparation for Further Processing:** Preparing materials for additional processes like milling, mixing, or chemical reactions.
6. **Quality Improvement:** Enhancing the stability and quality of the final product by controlling moisture content.

Applications of Drying

- A. **Food Industry:** Dehydrating fruits, vegetables, meat, and dairy products to increase shelf life.
- B. **Pharmaceuticals:** Drying drugs and medicinal powders to ensure stability and efficacy.
- C. **Agriculture:** Drying grains, seeds, and hay to prevent spoilage during storage.
- D. **Textiles:** Removing water from fabrics after washing or dyeing.
- E. **Chemicals:** Drying chemicals and intermediates to maintain purity and quality.
- F. **Construction:** Drying lumber, bricks, and other building materials.
- G. **Paper Industry:** Drying paper pulp to produce various types of paper products.
- H. **Ceramics:** Drying clay and ceramic products before firing.

Mechanism of the Drying Process


1. Heat Transfer:

- Heat is supplied to the material to increase its temperature and provide the energy needed for evaporation.
- This can be achieved through various methods such as conduction, convection, or radiation.

2. Mass Transfer:

- Moisture inside the material moves to the surface and evaporates into the surrounding air.
- This involves the diffusion of water molecules within the material and the movement of water vapor away from the surface.

Steps in the Drying Process



1. Initial Heating:

- The material is initially heated, and surface moisture begins to evaporate.

2. Constant Rate Period:

- The rate of drying remains constant as surface moisture continues to evaporate.
- This phase depends on the rate of heat transfer to the material.

3. Falling Rate Period:

- As surface moisture is depleted, internal moisture must migrate to the surface.
- The drying rate decreases as internal diffusion becomes the limiting factor.

4. Equilibrium Moisture Content:

- Drying continues until the material reaches its equilibrium moisture content, where the moisture content is in balance with the surrounding environment.


Factors Affecting the Drying Process

- 1. Temperature:** Higher temperatures generally increase the drying rate but can also affect the quality of heat-sensitive materials.
- 2. Humidity:** Lower ambient humidity levels enhance the drying process by increasing the vapor pressure gradient.
- 3. Airflow:** Increased airflow over the material surface helps remove evaporated moisture, enhancing the drying rate.
- 4. Material Properties:** The initial moisture content, permeability, and thickness of the material significantly influence the drying process.
- 5. Surface Area:** Greater surface area of the material exposed to air can increase the drying rate.

6. **Drying Method:** Different drying methods (e.g., air drying, vacuum drying, freeze drying) have varying efficiencies and suitability depending on the material and desired end product.

Equilibrium Moisture Content (EMC)

Measurements of Equilibrium Moisture Content



1. Hygroscopic Methods:

- **Static Equilibrium Method:** The material is placed in a controlled environment (constant temperature and relative humidity) until no further weight change occurs.
- **Dynamic Method:** The material is continuously exposed to a changing environment until equilibrium is reached, and the EMC is measured dynamically.

2. Gravimetric Methods:

- **Oven Drying:** A sample is weighed, dried in an oven at a specified temperature until constant weight is achieved, and then reweighed. The difference gives the moisture content.
- **Desiccator Method:** Similar to oven drying but uses a desiccator for removing moisture.

3. Electrical Methods:

- **Capacitance Sensors:** Measure the dielectric constant, which changes with moisture content.
- **Resistive Sensors:** Measure the electrical resistance, which varies with moisture content.

4. Chemical Methods:

- **Karl Fischer Titration:** A chemical reaction method that measures water content in the sample.

Applications of Equilibrium Moisture Content




FREE PREVIEW

[Click here to visit our website](#)

PHARMACY PREMIUM NOTES

Complete subject
and semesters are
available on
FirstHope app only.



[Scan or click here](#)

Click here to get the app



Available on Google Play

JOIN THE FIRSTHOPE COMMUNITY

Join our Telegram channel

Click here to join Telegram



[Scan or click here](#)

@FirstHopeNotes

Instagram

@firsthope.official

[Click here to follow >](#)

YouTube channel

FirstHope-Pharmacy / Live streams

[Click here to watch >](#)

WhatsApp channel

Follow FirstHope on WhatsApp

[Click here to join >](#)

FirstHope website

firsthopenotes.com

[Click here to visit >](#)

B.Pharm / D.Pharm / M.Pharm / Pharm.D

Preview notes. Complete subjects and semesters in the FirstHope app.